

# Full Height Turnstile

Wide interior curved design dual-way all stainless turnstile  
2.3M high.

SUS304 Stainless • Semi or Fully Automatic capabilities •  
IPX4 Protection • 5 Year Warranty • 10+ Years' Experience.

## Introduction

The full height turnstile is assembled to provide a ridged steel framework shell. Ideal for outdoor installations as it provides high durability and tensile strength. All parts made with SUS304 1.5-3.0mm stainless steel material to provide rustproof and high quality durability.

The turnstile can be set to be always be push revolved in an emergency, thus, allow unhindered passage.



**REH-6081**

## Technical Specifications

### General

Start-up Time	3s(semi-automatic),8s(full-automatic)
Time to open Gate	0.2 seconds
Direction	Single or bidirectional
Working environment	Indoor or outdoor
Ingress Protection	IP45
Pass speed	30~35 persons/minute
Operational life	>3 million
Working temperature	Indoor/outdoor (with a tent over) -10°C—50°C Relative humidity: ≤90%, no condensation
Communication Interface	RS485, TCP/IP.

### Physical

Dimensions	2400mm x 1350mm x 2300mm
Housing Material	SUS304 1.5-2.0mm stainless steel optional to use SUS316L
Weight	400 kg / 882 lb
Input interface	Dry contact signal or +12V level signal or DC12V pulse signal with a width of more than 100ms. Driving current: > 10mA

### Electrical

Working voltage	AC110/220 ±10% V/50 ±10% HZ (specify when ordering)
Electronic motor	Brushless motor 24V 40W with fully auto option
Power Consumption	6A

### Extra

Options.	SUS 316, Powder coating finish, coloured style for LEDs or. User RFID reader fitting cradle.
----------	--

## Standard Functionality

- » Alarm Function.
- » Passage width 650mm
- » High visible LED direction arrow plate.
- » Swipe card memory function.
- » External long-range management and control via computer.
- » Optional with Face detection biometric.
- » Two or Five-year warranty models.

## CAD Dimensions

